



Standard design

Manufactured acc. to DIN 16878 or prEN 14285

Length	6 m
Smooth ends	onesided with chamfer
Colour	black
Inner surface	smooth

Possible designs

Length	1 m to 6 m
Coloured stripes	co-extruded
Colour	on request
Outer surface	coloured, co-extruded or solid dyed
Inner surface	inner grooves for reducing the cable pull-in forces
Labelling	acc. to customer specifications

Item designation	Outer diameter (mm)	Wall thickness (mm)	SN type	Pallet contents (m)	Weight (kg/m)
KSR 110 x 3,4 GE	110	3,4	4	516	1,120
KSR 110 x 4,2 GE	110	4,2	4	516	1,370
KSR 110 x 4,7 GE	110	4,7	8	516	1,590
KSR 110 x 5,3 GE	110	5,3	16	516	1,770
KSR 110 x 6,3 GE	110	6,3	16	516	2,020
KSR 125 x 3,9 GE	125	3,9	4	408	1,450
KSR 125 x 4,8 GE	125	4,8	4	408	1,765
KSR 160 x 4,9 GE	160	4,9	4	234	2,320
KSR 160 x 6,2 GE	160	6,2	4	234	2,965
KSR 160 x 6,9 GE	160	6,9	8	234	3,350