



### Standard design

Manufactured acc. to DIN 16878 or prEN 14285

<b>Sleeve type</b>	integrally moulded plug-in sleeve (SM)
<b>Sealing ring</b>	compression lip sealing ring, type "SX" (inserted in the factory)
<b>Sharp end</b>	with plug-in depth marking and chamfer
<b>Length</b>	6 m
<b>Colour</b>	black
<b>Inner surface</b>	smooth

### Possible designs

<b>Length</b>	1 m bis 6 m
<b>Coloured stripes</b>	co-extruded
<b>Colour</b>	on request
<b>Outer surface</b>	fcoloured, co-extruded or solid-dyed
<b>Inner surface</b>	inner grooves for reducing the cable pull-in forces
<b>Labelling</b>	acc. to customer specifications

Item designation	Outer diameter (mm)	Wall thickness (mm)	SN type	Pallet contents (m)	Weight (kg/m)
<b>KSR 110 x 3,4 SM</b>	110	3,4	4	516	1,120
<b>KSR 110 x 4,2 SM</b>	110	4,2	4	516	1,370
<b>KSR 110 x 4,7 SM</b>	110	4,7	8	516	1,590
<b>KSR 110 x 5,3 SM</b>	110	5,3	16	516	1,770
<b>KSR 110 x 6,3 SM</b>	110	6,3	16	516	2,020
<b>KSR 125 x 3,9 SM</b>	125	3,9	4	408	1,450
<b>KSR 125 x 4,8 SM</b>	125	4,8	4	408	1,765
<b>KSR 160 x 4,9 SM</b>	160	4,9	4	234	2,320
<b>KSR 160 x 6,2 SM</b>	160	6,2	4	234	2,965
<b>KSR 160 x 6,9 SM</b>	160	6,9	8	234	3,350

\*ASM = attached plug-in sleeve