



### Standard design

Manufactured acc. to DIN 16875

**Length** 6 m

**Smooth ends** onesided with chamfer

**Colour** black / anthracite

### Possible designs

**Length** 1 m to 6 m

**Type** intermediate length and special colour on request

**Colour** special colours are available on request

**Labelling** acc. to customer specifications

Item designation	Outer diameter (mm)	Wall thickness (mm)			Pallet contents (m)	Weight (kg/m)
		Range 2	Range 3	Range 4		
<b>KSR 32 x 1,8 GE</b>	32			1,8	3.018	0,264
<b>KSR 50 x 1,8 GE</b>	50		1,8		1.200	0,422
<b>KSR 63 x 1,9 GE</b>	63		1,9		816	0,562
<b>KSR 63 x 3,0 GE</b>	63			3,0	816	0,854
<b>KSR 75 x 2,2 GE</b>	75		2,2		630	0,782
<b>KSR 75 x 3,6 GE</b>	75			3,6	630	1,220
<b>KSR 90 x 2,7 GE</b>	90		2,7		432	1,130
<b>KSR 110 x 2,2 GE</b>	110	2,2			300	1,160
<b>KSR 110 x 5,3 GE</b>	110			5,3	300	2,610
<b>KSR 125 x 2,5 GE</b>	125	2,5			204	1,480
<b>KSR 125 x 3,7 GE</b>	125		3,7		204	2,130
<b>KSR 125 x 6,0 GE</b>	125			6,0	204	3,340
<b>KSR 140 x 4,1 GE</b>	140		4,1		180	2,650
<b>KSR 160 x 3,2 GE</b>	160	3,2			160	2,400
<b>KSR 160 x 4,7 GE</b>	160		4,7		120	3,440
<b>KSR 160 x 7,7 GE</b>	160			7,7	120	5,470
<b>KSR 200 x 3,9 GE</b>	200				90	3,650