



Standard design

Manufactured acc. to DIN EN 61386-24

Type with outer corrugation and inner pipe

Type 450 N

Sleeve type Double plug-in sleeve, sand-tight design

Material PE-HD

Length 50 m in coils, with inside cable pull-in aid

Colour Outer surface black

Possible designs

Sleeve type double plug-in sleeve, water-tight design

Length on request

Colour red, yellow, blue, green or orange

Item designation	Dimensions			On rolls (m)
	DN	ø d _i (mm)	ø d _a (mm)	
VBR-F 40	40	30 ^{+2,0}	40 ^{+0,8}	50
VBR-F 50	50	40 ^{+2,0}	50 ^{+1,0}	50
VBR-F 63	63	50 ^{+2,0}	63 ^{+1,2}	50
VBR-F 75	75	60 ^{+2,0}	75 ^{+1,4}	50
VBR-F 90	90	74 ^{+2,0}	90 ^{+1,7}	50
VBR-F 110	110	93 ^{+2,0}	110 ^{+2,0}	50
VBR-F 120	120	102 ^{+2,0}	120 ^{+0,5/-0,5}	50
VBR-F 125	125	105 ^{+2,5}	125 ^{+2,3}	50
VBR-F 160	160	137 ^{+2,5}	160 ^{+2,3}	50